



AMB-N280S1

3.5" Intel N2800 SBC



Features

- Intel N2800 Processor with NM10 Chipset
- 1 x DDR3L-1066MHz, SO-DIMM, up to 4GB, non-ECC
- 6 x COM, 4 x USB 2.0, 1 x SATA II, 2 x mini PCIe, 2 x GbE
- mSATA Support



Specification

System

CPU	Intel Atom N2800 Dual Core 1.86GHz
Chipset	Intel NM10 PCH
Memory	1 x DDR3L-1066MHz, SO-DIMM, up to 4GB, non-ECC
BIOS	AMI
Hardware Monitoring	CPU voltage and temperature.
WatchDog Timer	Software programmable 1~255 sec.

Video

Graphic Controller	Intergrated Intel Graphics Media Accelerator 3650
Video Interface	<ul style="list-style-type: none"> • 1 x VGA (1 x DB15) • 1 x HDMI • 1 x 18-bit LVDS (1 x pin header)

Storage

SATA	1 x SATA II port
mSATA	1 x mSATA port (mini PCIe socket)

I/O

Ethernet	2 x GbE RJ45 with LED, RTL8111E
Expansion Slot	2 x mini PCIe socket
Serial Port	4 x RS-232(1 x 40-pin header) 1 x RS-232(1 x 3-pin header, only TX/RX) 1 x RS-232/485(1 x 3-pin header, only TX/RX)
USB	4 x USB 2.0 (4 x pin header)
GPIO	8-bit Digital I/O
Parallel Port	1 x LPT (1 x pin header)
Keyboard/Mouse	1 x JST 6-pin header
Audio	<ul style="list-style-type: none"> • Realtek ALC662 Audio Codec • MIC-in / Line-out (1 x pin header)

Power Requirement

Power Input	1 x 4-pin 2.54mm single 12V power input connector
-------------	---

Software

OS Support	Windows 7 32-bit, Fedora 14 32-bit
------------	------------------------------------

Mechanical & Environment

Dimension	146mm x 102mm (5.7" x 4")
Operating Temp.	0~55°C (32~131°F)
Storage Temp.	-20~80°C (-4~176°F)
Safety	CE, FCC compliant

Packing List

- 1 x AMB-N280S1
- 1 x Driver CD
- 1 x Quick Guide
- 1 x SATA Power Cable
- 1 x SATA Cable
- 1 x DC Power Cable
- 1 x 4 in 1 COM Cable (4 x DB9)

Ordering Information

AMB-N280S1	3.5" SBC with Intel N2800, NM10, DDR3, GbE, SATA II, USB 2.0, COM
------------	---

Dimension

