


AMB-BT18T2

Intel Bay Trail SoC, 1 x VGA, 1 x HDMI, 1 x LVDS, 2 x GbE, 6 x COM, 9 x USB 2.0, 1 x mini PCIe, 1 x SATA II, 1 x mSATA



Features

- Intel Bay Trail SoC, low power consumption.
- 1 x DDR3L-1333MHz, SO-DIMM, up to 8GB
- 9 x USB 2.0
- 4 x RS232, 1 x RS232/485, 1 x RS232/TTL
- 2 x GbE LAN, 1 x mini PCIe, 1 x SIM slot
- 1 x SATAII, 1 x mSATA
- 12V Input
- Fanless design



CE FC

Specification

Specification

CPU	1. Intel® Celeron® J1800, Dual-Core, 1M Cache, 2GHz (2.41GHz), 10W(AMB-BT18T2)
Chipset	Intel Bay Trail SoC
Memory	1 x DDR3L-1333MHz, SO-DIMM, up to 8GB
BIOS	AMI UEFI BIOS
Real Time Clock	1 x System RTC

Video

Graphic Controller	Intel® HD Graphics
Video Interface	<ul style="list-style-type: none">• 1 x VGA, resolution up to 2560x1600 @ 60Hz• 1 x HDMI, resolution up to 1920x1080 @ 60Hz• 1 x LVDS (24 Bit Dual channel LVDS, resolution up to 1920x1200 @ 60Hz)

Storage

SATA	1 x SATA II Port + 1 x mSATA
------	------------------------------

I/O

Ethernet	2 x GbE LAN
Expansion Slot	1 x mini PCIe
Ethernet Chip	2 x Realtek GbE LAN Chip (8105E/8111E)
Serial Port	4 x RS232 + 1 x RS232/RS485 + 1 x RS232/TTL
Parallel Port	1 x Parallel Port
USB	9 x USB2.0 (4XReal I/O + 5 x Pin Header.)
Audio	Realtek ALC662 5.1-channel High Definition Audio 1 x Line-out, 1 x MIC-in
GPIO	8 x GPIO
Keyboard	1 x PS/2 connector for Key Board/Mouse
SIM	1 x SIM slot

Power Requirement

Power Input	2 x 4-Pin AT power connector
Power Output	DC 12V/5V power output Connector, System Fan & CPU Fan connector

Software

OS Support	Window 7 (32bit/64bit), windows 8.1(32bit/64 bit), windows10
------------	---

Mechanical & Environment

Dimension	170mm x 170mm (6.69" x 6.69")
Operating Temp.	0~60°C
Storage Temp.	-20~75°C
Safety	RoHS


Packing List

- AMB-BT18T2
- Quick User Guide
- Driver CD
- SATA Cable
- SATA Power Cable
- 3 x COM Cable
- VGA Cable

Ordering Information

AMB-BT18T2	Intel Celeron J1800, Dual Core, 1M cache, 2GHz (2.41GHz), 1 x VGA, 1 x HDMI, 1 x LVDS, 2 x GbE, 6 x COM, 9 x USB2.0, 1 x mini PCIe, 1 x SATA, 1 x mSATA
------------	---

Dimension



I/O Connectors

