



## Features

- ✓ Intel GME965 with Core 2 Duo, Celeron M
- ✓ 3 x Battery Backup SRAM 512KB
- ✓ Selected Write Protect EEPROM up to 4MB
- ✓ VGA/DVI-D
- ✓ TPM1.2/iButton/Jurisdiction ROM
- ✓ 5.1 Audio Channel with 6W Amplified
- ✓ PCI Express x16 Slot
- ✓ Optional Smart Card Reader Module

## Specification

Invention Patent I334065

### General PC Feature

<b>CPU</b>	<ul style="list-style-type: none"> <li>• Intel Core 2 Duo 2.20GHz</li> <li>• Intel Celeron M 2.0GHz</li> </ul>
<b>Chipset</b>	Intel GME965 + ICH8M
<b>Front Side Bus</b>	533/667/800MHz
<b>Memory</b>	<ul style="list-style-type: none"> <li>• 1 x 200-pin SO-DIMM socket support 533/667MHz Dual Channel DDR2 SDRAM up to 2GB</li> <li>• Onboard 512MB DDR2 SDRAM</li> </ul>
<b>Battery</b>	<ul style="list-style-type: none"> <li>• 1 x 220 mAh battery for system RTC</li> <li>• 3 x 140 mAh re-chargeable batteries for SRAM, Second RTC, Intrusion Logger</li> </ul>
<b>Real Time Clock</b>	1 x system RTC and 1 x secured RTC
<b>Video</b>	
<b>Graphic Controller</b>	Intel GME965 integrated GMA X3100 graphic controller
<b>Video Memory</b>	DVMT 4.0, Maximum 384MB shared
<b>Video Interface</b>	<ul style="list-style-type: none"> <li>• 1 x VGA (1 x DB15)</li> <li>• 2 x DVI-D port</li> </ul>
<b>PCI Express Slot</b>	1 x PCI Express x16 slot
<b>Storage</b>	
<b>SATA</b>	3 x SATA II port
<b>CF</b>	2 x Compact Flash Type I/II socket support UDMA
<b>Communication</b>	
<b>Ethernet</b>	2 x Gbps RJ45 with LED, Intel 82574L
<b>USB</b>	8 x USB2.0 (4 x external port, 4 x pin header)
<b>Serial Port</b>	<ul style="list-style-type: none"> <li>• 3 x RS-232</li> <li>• 2 x RS-232/ccTalk</li> <li>• 2 x RS-232/TTL</li> <li>• 2 x RS-232/422/485</li> </ul>
<b>Audio</b>	
<b>Output</b>	5.1 channel
<b>Amplifier</b>	6 Watts per channel
<b>Volume Channel</b>	Left channel
<b>Other Feature</b>	
<b>Hardware Monitoring</b>	<ul style="list-style-type: none"> <li>• CPU Voltage</li> <li>• CPU and system temperature</li> <li>• CPU and fan speed</li> <li>• System fan speed control</li> </ul>
<b>WatchDog Timer</b>	Software programmable 1~255 sec.
<b>Indicator</b>	HDD and Power LED
<b>Gaming Function</b>	
<b>Digital Input</b>	<ul style="list-style-type: none"> <li>• 32 x optical isolated input</li> <li>• State change interrupt</li> </ul>
<b>Digital Output</b>	32 x 500 mA digital output
<b>Readable DIP Switch</b>	1 x 8-bit DIP switch

### Gaming Function

<b>GPIO (TTL Level)</b>	-
<b>Timer</b>	4 x 16-bit timers with time out interrupt
<b>Battery backup SRAM</b>	<ul style="list-style-type: none"> <li>• 3 x 512KB</li> <li>• 140 mAh rechargeable battery</li> <li>• Battery voltage low log and voltage readback</li> </ul>
<b>EEPROM</b>	2K Bytes
<b>Jurisdiction Chip</b>	8 x PLCC ROM socket
<b>Intrusion Logger</b>	<ul style="list-style-type: none"> <li>• 1 x chassis intrusion switch + 2 bits on golden fingers</li> <li>• 10 events with time stamps</li> <li>• 140 mAh rechargeable battery</li> <li>• battery voltage low log and voltage readback</li> </ul>
<b>Chassis Intrusion Switch</b>	1 x switch on system chassis
<b>Smart Card Reader</b>	-
<b>Reel Mechanism Control</b>	-
<b>Smart Hard Meter</b>	8 x smart hard meter outputs
<b>Random Number Generator</b>	16 bits
<b>Security</b>	iButton socket, ProtectU, TPM 1.2
<b>Power Requirement</b>	
<b>Power Input</b>	10-pin ATX power connector
<b>Power Consumption</b>	-
<b>Software</b>	
<b>OS Support</b>	Windows XP/XP Embedded, Linux
<b>Software Development Kit</b>	<ul style="list-style-type: none"> <li>• Device driver</li> <li>• Application Program Interface (API)</li> <li>• Demo program</li> </ul>
<b>Mechanical &amp; Environment</b>	
<b>Thermal Design</b>	CPU fan
<b>Chassis Material</b>	SPGC steel
<b>Dimension (W x H x D)</b>	259mm x 161mm x 247mm (10.20" x 6.34" x 9.73")
<b>Weight</b>	-
<b>Operating Temp.</b>	-10~60°C (14~140°F)
<b>Storage Temp.</b>	-20~80°C (-4~176°F)
<b>Relative Humidity</b>	0 to 90% @ 40°C, non-condensing
<b>Safety</b>	CE, FCC class A
<b>Packing List</b>	
<ul style="list-style-type: none"> <li>• 1 x ACE-S5600FL</li> <li>• 1 x Software driver CD</li> <li>• 1 x Quick user's manual</li> </ul>	
<b>Ordering Information</b>	
<b>ACE-S5600T75</b>	ACE-S5600FL with Intel Core 2 Duo 2.20GHz
<b>ACE-S5600CM55</b>	ACE-S5600FL with Intel Celeron M 2.0GHz